



NUMERixx³-G 1" fem-G 1" fem

oval gear meter-digital

Item number: 23 190
EAN: 4048358231901

Technical data

Distance in-/out flange (mm): 95
Connection: G 1" female
Media: diesel, fuel oil, selflubricating low viscosity liquids
Flow capacity min. (l/min): 2
Flow capacity max. (l/min): 100
Pre-set flow direction: horizontal
Permitted liquid temperature max. (°C): 40
Permitted ambient temperature (°C): -10 / +60
Measuring accuracy (%): 0,5
Nominal pressure (bar): 3,5
Burst pressure (bar): 28
Battery lifetime: approx. 2 years at 0.5 hours per day (20 °C)
Materials of parts in contact with liquid
Meter housing: AISi 12 (sea water resistant)
Oval gears: POM
Seals: NBR 70
External dimensions LWH (mm): 100 x 100 x 65
Weight (kg): 0,58

Specification

- Totalisator for daily operation 5-digits with floating decimal, resettable to zero, partition 0,000 up to 99999
- Totalisator 6 digits with floating decimal, partition 0,0 up to 999999

Special notes

- Easy to read 5-digits display
- Resettable display
- The metering precision can be adjusted to the viscosity using the calibration scale
- The user can adjust the following indicating units: Litres, gallons, pints, quarts
- Displays: Indication of partial quantity equals current filling level (resettable to zero) + total quantity (resettable to zero) + total quantity (not resettable to zero)

Packaging

Dimensions LxWxH (mm): 145 x 126 x 78
Weight including package (kg): 0,67
Packing unit: 1,0